

T-EASY desks



QUALITY STANDARD

- LST EN 527-1:2011
- LST EN 527-2:2003

TECHNICAL INFORMATION

Desktop

- 25 mm MFC (melamine) with 2 mm ABS edging;
- With or without a cut-out for grommet and wire management;
- With or without a scallop for wire management.

Adjustable telescopic frame

- Side support steel L shape 50x30x460 mm;
- Square steel pipe 50x25x554 mm;
- Steel pipe part for adjustment 40x20x920 mm;
- Adjustment range - 600 mm;
- Powder coated metal, matches the colour of columns and feet.

Columns

- Metal tube - 80x40 mm;
- Powder coated metal.

Feet type W




- Metal sheet 700x70x30 mm with welded profile for stability;
- Height - 30 mm;
- Plastic feet with height levelling (+10 mm);
- Powder coated metal; matches the colour of frame.

Feet type I








- Metal tube – 796x60x30 mm;
- Plastic feet with height levelling (+10 mm);
- Powder coated metal; matches the colour of frame.

RANGE



W 1116–1716
D 700, 800
H 715



Must be ordered

(for desktops with cut-out)



Metal grommet:
317x119 mm,
H=27 mm

Optional




Cable trays



Power socket
blocks



Cable ducts



Felt-lined metal
drawers with lock